



## CTA EXPRESS

ES

Se puede utilizar como punto de anclaje conforme a la norma EN795

Las cintas de anclaje, son puntos de anclaje conseguidos a partir de cintas de. Su ligereza, versatilidad y diferentes tamaños, hacen que sean los anclajes más utilizados y polivalentes.

Además, han sido certificadas también conforme EN 354, como cinta de conexión.

|               |                  |     |     |     |     |
|---------------|------------------|-----|-----|-----|-----|
| Norma         | EN 795B - EN 354 |     |     |     |     |
| Peso (g)      | 80               | 110 | 140 | 170 | 220 |
| Longitud (cm) | 60               | 90  | 120 | 150 | 200 |
| Resistencia   | 22 kN            |     |     |     |     |

### CARACTERÍSTICAS

|          |           |
|----------|-----------|
| Material | Poliamida |
| Ancho    | 20mm      |








## CTA EXPRESS

It can be used as anchorage point in conformity to the norm EN795.

Anchorage straps and wire ropes are anchorage points made from polyester webbing straps or 8mm steel wire ropes. Their light-ness, versatility and different lengths, make them the most frequently used and polyvalent anchorage devices.

In addition, they have also been certified as a connecting lanyard in conformity to EN 354.

|             |                                                                                     |                                                                                       |                                                                                       |                                                                                       |                                                                                       |
|-------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Norm        | EN 795B - EN 354                                                                    |                                                                                       |                                                                                       |                                                                                       |                                                                                       |
| Weight (g)  | 80                                                                                  | 110                                                                                   | 140                                                                                   | 170                                                                                   | 220                                                                                   |
| Colour      |  |  |  |  |  |
| Length (cm) | 60                                                                                  | 90                                                                                    | 120                                                                                   | 150                                                                                   | 200                                                                                   |
| Resistance  | 22 kN                                                                               |                                                                                       |                                                                                       |                                                                                       |                                                                                       |

### FEATURES

|          |           |
|----------|-----------|
| Material | Polyamide |
| Width    | 20mm      |